

# Maco Door Lock (Single Door)

## Multi-point security locking system

### Suitable for use on PVCu, timber or aluminium doors with a 16mm PVCu type eurogroove

Maco Door Locks are operated by internal and external lever handles. The G-TS door lock has a standard lift lever operation and the W-TS lock has a split spindle operation making it more suitable for some front door applications.

Z-TS operated door lock for front door applications when a fixed

external pad handle is required. 20mm throw top and bottom shootbolt extensions can be fitted on most lock styles and are suitable for both residential and double door applications.

Maco Door Locks are available with compression cams for increased weather performance.

### Features and Benefits

- Available in 92mm handle centres
- 28, 35 & 45mm backset versions available for the G-TS
- 35 & 45mm backset versions available for the Z-TS & W-TS
- Non-handed lock with reversible latch
- Dead bolt as standard
- Range of variants offer various levels of security
- Suitable for door sizes up to 2400mm in height (other sizes available on request)



### Details

#### Mushroom bolt

Adjustable security mushroom bolt for enhanced security

#### Finger bolt

20mm throw finger bolt for high security applications

#### Hook bolt

For the highest possible level of security

#### Striker plates

Produced from high quality zinc and steel, adjustable with a 4mm Allen key

#### Manufactured from

Produced from high quality zinc and steel

#### Recommended screws

No.8 countersunk or equivalent. For Tricoat finish ensure Tricoat screws are used

#### Standards

PAS 24 and BS6375 Parts 1 & 2

#### Finishes

Silver chromate  
Tricoat (high corrosion resistance) also available

#### More information

enquiries@titon.co.uk / 01206 713801

