

# WSFK Range

## Shower Fan Kits

### For Toilets, Shower Rooms, Bathrooms and Utility Rooms

- For ceiling installation
- With or without timer
- Three sizes
- Complete Kit



- Axial fans designed to extract from toilets, shower cubicles and bathrooms
- Timer or Non-Timer
- Kit contains:
  - In-Line Duct Fan
  - Mounting Bracket (4"/10cm version only)
  - Inside and outside grilles
  - 3m length of PVC flexi-duct (4"/10cm, 5"/12cm or 6"/15cm dia)
  - Screws, plugs and cable ties.
- Made of shock proof and heat-resistant plastics
- Motors have sealed, self lubricating bearings for long life
- Protected with thermal cut-out
- Maximum ambient temperature of 40°C
- Double Insulated
- Fans comply with EC Low Voltage Directive and EC Directives EMC89/336, BSEN60529, BS800 and BS3456
- Fans are CE marked
- Exceed current Building Regulation requirements

Model	m <sup>3</sup> /hr	litres/sec	Max mmH <sub>2</sub> O	Max Pa	Voltage	Hz	Watts	dbA
SFK100	98	27	3	29	230	50	15	41
SFK125	190	53	5	49	230	50	20	43
SFK150	320	89	8	98	230	50	25	43