

Gas Regulations Maxiglaze Glazed In Ventilator

Specifier's Text

Windows to be fitted with glazed in ventilators, Titon Maxiglaze Gas Regulations version, in accordance with BS 5440 Part 2 and Building Regulations Approved Document J. Ventilators to give 4000mm² available air opening (AAO) at 268mm overall vent length, 5000 mm² AAO at 315mm overall vent length, 7500 mm² AAO at 455mm overall vent length, and 10000mm² AAO at 574mm.

Glazed-in ventilator to suit 20, 24 or 28mm glass thickness and be constructed from aluminium, thermally improved by crimped-in PVCu extrusions and an integral canopy with PVCu or aluminium option. Product is to be available in made to measure or bar length form and capable of one colour internally and another externally.

Ventilator to be sealed to glass unit using patented Vent Injection Process (VIP).

Product to be glazed in accordance with manufacturer's instructions and using manufacturer's gaskets.

Product to be supplied with advisory labels.

Product to be manufactured under BS EN ISO 9001.

Ventilator available from Titon Hardware Limited

TITON CANNOT ADVISE ON THE CORRECT SIZING OR USAGE OF GAS REGS VENTILATORS, PLEASE REFER TO A QUALIFIED GAS PROFESSIONAL FOR ADVICE.