

Titon SF Ventilator

Specifier's Text

Windows to be fitted with slot ventilator(s), Titon SF Ventilator and Canopy, that, when used in the correct quantities, will comply with background ventilation requirements of either of following:

Approved Document F 'Ventilation'- Building Regulations, England & Wales.

Part K 'Ventilation of Buildings' - Technical Standards, Scotland.

Technical Booklet Part K 'Ventilation' - Building Regulations, Northern Ireland.

Technical Guidance Document Part F 'Ventilation' - Building Regulations, Republic Of Ireland.

Ventilator and canopy to be available in 2000, 3000, 4000, 6000, 6500 or 8000mm² available air opening sizes or supplied in bar length for cutting to size by customer. Ventilator to incorporate a deflector (upward or downward) that provides infinitely variable opening. Product can be supplied in any RAL colour for matching to window section and should be able to be supplied in mill finish for painting by customer.

Ventilator and canopy to fit over 13mm wide slot(s), the ventilator will feature a gasket for optimum weathering performance and have a positive closure action. Ventilator and canopy to be produced from aluminium extrusion, the canopy to incorporate grille and sealant groove, and both shall incorporate screw covers.

For use on PVCu or aluminium windows.

Ventilator and canopy shall have been manufactured under BS EN ISO 9001 and be offered with a 10 year guarantee on request.

Ventilator and canopy available from Titon Hardware Limited.